

System Stripper SLOTOSTRIP 10

System Stripper SLOTOSTRIP 10 system stripper is a stabilized, chemically operating, no complexing agent containing spraying process on the basis of organic acid and hydrogen peroxide (H₂O₂) for the removal of metal resist layers made of tin.

Tin can also be stripped from gold plugs or gold plated PCBs without any problems. The stripper can be recycled in a by-pass operation. It is only necessary to replenish the drag-out of acid and the hydrogen peroxide content which is necessary for tin dissolution.

The metal absorption of the stripper without recycling is approx. 120 - 140 g/l of tin. The copper etch rate is very low.

The stripper contains no nitric acid and no fluoride.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instructions carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

