

# Aluminium Pickle

## ALB 100

Aluminium Pickling Process ALB 100 is a simple dipping process for aluminium and aluminium alloys to allow electroplating. It is preferably used for parts to be subsequently electro or electroless plated e.g. before nickel plating.

Pre-treatment with Aluminium Pickling Process ALB 100 does not influence the corrosion protection which is provided by subsequent deposited metal coatings. The final coating on electro plated aluminium parts must be sufficient thick and pore-free deposited if the parts will be exposed to humidity.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

