

Aluminium Pickle SLOTETCH 590

Aluminium Pickle SLOTETCH 590 is a strongly acidic solution for the activation of aluminium alloys.

It is specially formulated to have a low etch rate, allowing for complete removal of aluminium oxides, without deep etching of the substrate. This avoids the formation of heavy smuts.

- Provides a mild uniform etch on all aluminium alloys
- Helps reduce the possible formation of nodules and pits in subsequent surface finishing or plating steps
- Improves adhesion of the electroless nickel or other deposit

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.