

Degreaser

SLOTOCLEAN AK FSA

The Degreaser SLOTOCLEAN AK FSA is a mild alkaline cleaner for immersion or spray cleaning of aluminium, aluminium alloys and zinc die-casts. Removal of paste from polished zinc die-cast must be supported by ultrasonic.

Degreaser SLOTOCLEAN AK FSA is also suitable for degreasing of copper and brass, and to a certain extent for steel.

Nearly non-foaming when operated at temperatures > 60 - 70 °C is an outstanding feature of Degreaser SLOTOCLEAN AK FSA and is therefore especially recommended for application in spray plants. Additional surfactants should not be added as they would disable this feature.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

