

Cleaner

SLOTOCLEAN S 80

The Cleaner SLOTOCLEAN S 80 is based on sulphuric acid and is primarily used for the cleaning of printed circuit boards prior to activation.

Cleaner SLOTOCLEAN S 80 is low-foaming.

Cleaner SLOTOCLEAN S 80 only slightly affects copper surfaces. No residues of the cleaner remain on the surface.

Cleaner SLOTOCLEAN S 80 does not contain any alkylphenoethoxylate and is free of AOX.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

