

Degreaser SLOTOCLEAN AK 150

Degreaser SLOTOCLEAN AK 150 is a strongly alkaline process for immersion degreasing of steel. It is suitable for rack and barrel applications and is especially recommended for the removal of processing oil.

The Degreaser Salt SLOTOCLEAN AK 151 contains sodium hydroxide, only little silicate but does not contain any phosphates or complexing agents.

Although the Degreaser SLOTOCLEAN AK 150 does already contain surfactants, the additional use of a degreaser additive may be required for heavily contaminated parts. Schlötter offers a wide range of additives to enhance cleaning. Please refer to operating data sheet no. 02300 for an additive summary and their different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.