

# Degreaser

## SLOTOCLEAN AK 160

The Degreaser SLOTOCLEAN AK 160 is a universal alkaline process for degreasing of steel and non-ferrous metals, with good wetting and rinsing behaviour.

The excellent conductivity of Degreaser SLOTOCLEAN AK 160 allows both, application as immersion or hot-soak degreaser with optional ultrasound or air agitation support, and application as electrolytic degreaser.

The Degreaser SLOTOCLEAN AK 160 is operated with two components: Degreaser Salt SLOTOCLEAN AK 161 and a degreaser additive according to the assigned task.

Schlötter offers a wide range of additives to enhance cleaning. Please refer to operating data sheet no. 02300 for an additive summary and their different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.