

Degreaser SLOTOCLEAN AK 180

The Degreaser SLOTOCLEAN AK 180 is a weakly alkaline cleaner for the cleaning of non-ferrous metals, steel and aluminium. Make-up is performed with liquid concentrates.

SLOTOCLEAN AK 180 is recommended in combination with ultrasonic support if grinding and polishing residues have to be removed, immersion degreasing in case of processing oils.

SLOTOCLEAN AK 180 is operated with two components: Degreaser Concentrate SLOTOCLEAN AK 181 and a degreaser additive chosen according to the assigned task. Our operating data sheet (ODS) 02300-E Summary Degreaser Additives informs you about the different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

