

# Degreaser

## SLOTOCLEAN AK 2220

The Degreaser SLOTOCLEAN AK 2220 is a mildly alkaline immersion degreaser for steel, non-ferrous metals and aluminium.

The Degreaser SLOTOCLEAN AK 2220 is excellently suitable for the removal of processing oils and pigmented drawing compounds that require a weak alkaline product. The degreaser is very effective even at moderate temperatures and features excellent rinsing behaviour.

In plants with a high bath load separate dirt compartments are recommended, respectively oil separators in case of strong drag-in of oil. The Degreaser SLOTOCLEAN AK 2220 is particularly suitable for this type of application.

Degreaser SLOTOCLEAN AK 2220 may be used on its own or it may be supported by replenishment with a degreaser additive according to the assigned task. Schlötter offers a wide range of additives to enhance cleaning. Please refer to operating data sheet no. 02300 for an additive summary and their different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.