

Degreaser SLOTOCLEAN EL DCG-F

The Degreaser SLOTOCLEAN EL DCG-F is a universal cleaning process for electrolytic degreasing of steel, non-ferrous metals and zinc die-cast and is supplied as liquid concentrate.

Iron or steel components are cleaned anodically. Zinc die-cast and non-ferrous metals are first of all degreased cathodically, and are then activated by brief anodic poling. The anodic and the cathodic cleaning of non-ferrous metals and zinc die-casts should be carried out in separate tanks.

Combined with additives that enhance cleaning, the Degreaser SLOTOCLEAN EL DCG-F may also be used as immersion degreaser.

Schlötter offers a wide range of additives to enhance cleaning. Please refer to operating data sheet BATH 02300-E for an additive summary and their different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

