

# Antirust SLOTOCLEAN AC

Antirust SLOTOCLEAN AC is used as temporary corrosion protection for metal items.

Antirust SLOTOCLEAN AC is recommended on parts that are temporarily stored between cleaning and further processing.

Antirust SLOTOCLEAN AC is a viscous, aqueous product added to the warm rinse just before the parts are dried. It is important that no other rinsing follows after the warm rinse with Antirust SLOTOCLEAN AC so that the excellent anticorrosive effect isn't reduced.

The not disturbing film layer can be lacquered and easily be removed with a warm, alkaline degreaser solution.

Antirust SLOTOCLEAN AC does not contain any alkyl phenol ethoxilate and is free of AOX.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

#### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

