

Degreaser

SLOTOCLEAN EL 370

The Degreaser SLOTOCLEAN EL 370 is a universal cleaning process for electrolytic degreasing of steel and non-ferrous metals and is suitable for lead bronzes as well.

Iron or steel components are poled anodically. Non-ferrous metals are first of all degreased cathodically, and are then activated by brief anodic poling. The anodic and the cathodic treatment of non-ferrous metals should be carried out in separate tanks.

Schlötter offers a wide range of additives to enhance cleaning. Please refer to operating data sheet no. 02300 for an additive summary and their different possible combinations.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.