

# Degreaser SLOTOCLEAN AK 380

The Degreaser SLOTOCLEAN AK 380 is a strong alkaline immersion cleaner for steel. It is also suitable for cleaning of copper and copper alloys, although brass may slightly tarnish with extended treatment times. Although the Degreaser SLOTOCLEAN AK 380 is not suitable for zinc and aluminium, as it would affect their surface.

Degreaser SLOTOCLEAN AK 380 is operated with one component which contains all substances required for operation.

The surfactant combination of the Degreaser SLOTOCLEAN AK 380 acts demulsifying and is therefore especially suitable for plants with gravity oil separators respectively ultrafiltration systems, and therefore additional surfactants should not be added.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

#### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

