

# Bright Copper ACG 8

Bright Copper ACG 8 is an easy to operate electrolyte. The brightness and excellent levelling of the copper layers deposited from this electrolyte as well as the high deposition rate are the features of Bright Copper ACG 8. The copper coatings have low internal stress, are ductile and soft and can be easily polished. Well mechanically prepared steel parts can normally be bright nickel- and chrome plated directly after copper-plating without intermediate polishing.

Bright Copper ACG 8 is also suitable for thick copper plating of electroformings. Bright Copper ACG 8 isn't sensible to impurities.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

#### Important:

Please read these instructions carefully and follow recommendations given. We reserve the right to make technical changes as necessary. In the interests of safety, please pay attention to the R- and S- phrases on the labels of the containers. The minimum shelf life of the additives is printed on the label of the container. The current IMDS number of the layer deposited from the process can be found on the internet at [www.schloetter.com/downloads](http://www.schloetter.com/downloads).

For the storage of chemical products only the TRGS 514 and TRGS 515 regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid **for transportation** and must not be applied to storage.

