

Superbright Nickel SLOTONIK 40

Superbright Nickel SLOTONIK 40 offers all the demands of a modern bright nickel plating electrolyte. The deposits are fully bright and highly ductile with excellent throwing power and levelling even with thin deposits and they are also receptive to chrome plating.

Superbright Nickel SLOTONIK 40 is easy to operate and can be air- or mechanically agitated.

With the given additive system, it's possible to add the brightener and the leveller separately making it possible to generate reproducible brightness and levelling over a wide range and according to individual requirements of the user.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

