

# Post-Dip Solution SLOTOPAS NT 10

The Post-Dip Solution SLOTOPAS NT 10 is applied on already passivated zinc-nickel coatings.

Post-Dip Solution SLOTOPAS NT 10 is an alternative to usually applied sealings on black passivated layers and makes them less sensitive to touching, abrasion and scratches.

Transparent passivated zinc-nickel coatings treated with Post-Dip Solution SLOTOPAS NT 10 become almost insensitive to fingerprints. This simplifies the handling of the parts enormously.

SLOTOPAS NT 10 is a purely inorganic post-treatment which can be applied if organic based sealers are forbidden e. g. pipes.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

#### Important:

Please read these instructions carefully and follow recommendations given. We reserve the right to make technical changes as necessary. In the interests of safety, please pay attention to the R- and S- phrases on the labels of the containers. The minimum shelf life of the additives is printed on the label of the container. The current IMDS number of the layer deposited from the process can be found on the internet at [www.schloetter.com/downloads](http://www.schloetter.com/downloads).

For the storage of chemical products only the TRGS 514 and TRGS 515 regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) is only valid **for transportation** and must not be applied to storage.

