

# Post-Dip Solution SLOTOFIN 90

The Post-Dip Solution SLOTOFIN 90 is used for post-treatment of passivated zinc- and zinc alloy surfaces.

After drying, a clear transparent protective layer is obtained which is resistant to both fingerprinting as well as corrosion and improves the optical appearance. The post-dip solution moves evenly on the parts and leaves no film or unsightly drop-shaped residues.

By the treatment with Post-Dip Solution SLOTOFIN 90, blue passivated zinc and transparent passivated zinc alloy coatings result in a uniform almost transparent appearance.

A hot soak degreaser combined with suitable degreasing additives can remove post-dip residues from racks or centrifuge baskets. Therefore we recommend the products of our SLOTOCLEAN series.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

**Important:**

Please read these instructions carefully and follow recommendations given. We reserve the right to make technical changes as necessary. In the interests of safety, please pay attention to the R- and S- phrases on the labels of the containers. The minimum shelf life of the additives is printed on the label of the container. The current IMDS number of the layer deposited from the process can be found on the internet at [www.schloetter.com/downloads](http://www.schloetter.com/downloads).

For the storage of chemical products only the TRGS 514 and TRGS 515 regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid **for transportation** and must not be applied to storage.

