

# Yellow Passivation SLOTOPAS G 20

SLOTOPAS G 20 is a Cr(VI)-free passivating process for electroplated zinc coatings. Yellow Passivation SLOTOPAS G 20 is an immersion process and produces yellow-reddish/green protective layers on zinc coatings. The corrosion resistance is excellent and is equivalent to the protecting effects of a yellow-chromating electrolyte based on Cr(VI).

Tempering of the protection layer up to temperatures of  $\geq 80$  °C does not affect the corrosion protection quality, compared to yellow chromated (Cr(VI) zinc surfaces.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

#### Important:

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the TRGS 514 and TRGS 515 Regulations must be followed. The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.

